



## NIGHT VISION BINOCULAR

## NVB5X-3A

The NVB5 is a powerful night vision bi-ocular. They are weather and fog resistant and can withstand the rigors of almost any environment. The NVB will give you the range and clarity that other bi-oculars simply can not touch.

- Incredible 5x magnification
- Multi-coated, all-glass optics
- Detachable Long Range infrared illuminator
- Weather and fog resistant
- Limited Two-Year Warranty

### ACCESSORIES



Long range IR-450 Included



### SPECIFICATIONS

TOTAL DARKNESS TECH	Standard
MAGNIFICATION	5x
LENS SYSTEM	F112 mm
PROSHIELD LENS COATING	Yes
FOV	8°
RANGE OF FOCUS	30 m to infinity
DIOPTRER ADJUSTMENT	-5 to +5
CONTROLS	Digital
AUTOMATIC BRIGHTNESS CONTROL	Yes
BRIGHT LIGHT CUT-OFF	Yes
INFRARED ILLUMINATOR	Yes
IR INDICATOR	Yes (in FOV)
LOW BATTERY INDICATOR	Yes (in FOV)
POWER SUPPLY	1 x 1.5 V AA type battery or 1 x 3 V CR123A type battery
BATTERY LIFE	50 hours (17 hours w/IR illuminator)
ENVIRONMENTAL RATING	Weather and fog resistant
OPERATING TEMPERATURE	-40 to +50 °C
STORAGE TEMPERATURE	-50 to +70 °C
DIMENSIONS	288x108x102 mm / 11.3"x4.3"x4"
WEIGHT	1.32 kg / 2.9 lbs

### TUBE SPECIFICATIONS

#### HIGH QUALITY 3A GEN IMAGE INTENSIFIER TUBE

DESCRIPTION	Select Alpha
GENERATION	3
PHOTOCATHODE TYPE	Thin Film GaAs
RESOLUTION, lp/mm *	64-72
SIGNAL TO NOISE RATIO*	26 Typical
FIGURE OF MERIT	1800 Typical
MTTF - MEAN TIME BEFORE FAILURE, hours	10,000
EXPORT	N/A for Export

\* Specifications are provided for informational purposes only. Actual values may vary

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

1341 San Mateo Ave,  
South San Francisco, CA 94080.

[www.atncorp.com](http://www.atncorp.com)  
e-mail: [sales@atncorp.com](mailto:sales@atncorp.com), [info@atncorp.com](mailto:info@atncorp.com)

Tel: 800-910-2862, 650-989-5100,  
fax: 650-875-0129