



## NIGHT VISION GOGGLES

## NVG7-3

- HEAD MOUNTED FOR HANDS-FREE USE
- COMPACT AND LIGHTWEIGHT
- INTERCHANGEABLE LENSES FOR DIFFERENT MAGNIFICATIONS
- BUILT IN INFRA-RED ILLUMINATOR

Lightweight, rugged and a top notch performer the NVG-7 is an exceptional choice for hands-free usage. High-resolution image intensifier, auto-brightness, and bright source shut-off. NVG-7 goggles also have a build-in IR for total darkness with indicator ON light within the FOV and flip. One AA, case and manual are included. ATN NVG-7 is an excellent choice for hands-free night vision applications.

### STANDARD ACCESSORIES include:

- Flip-up Head Mount Assembly** - Allows for hands-free operation
- Brow Pads** - Changeable pads for secure head mount fit
- Eye Cups** - Prevents the emission of stray light or facial reflections
- Soft Carrying Case** - Provides convenient storage
- Shoulder Strap** - Attached to the NVG-7 carrying case for easy portability
- Microfiber Lens Cleaning Cloth** - Used to safely clean the objective and eyepiece glass surfaces
- Day Light Filter** - Filters excessive light. Protects objective lens from the elements
- Operator's Manual** - Instructional user's guide
- Batteries** - One (1) 3V Lithium CR123A or one (1) 1.5V AA type.

- Lightweight, compact rugged Goggle system
- Multi-purpose: Hand-held, head-mounted or helmet-mounted
- Comfortable, flip-up headgear
- Multi-coated all-glass optics
- Wide angle infrared illuminator
- Optional 3x, 5x and 10x lenses available
- Water and fog resistant
- Limited Two-Year Warranty

### SPECIFICATIONS

Magnification	1x
Lens System	F1.2, 26 mm
Proshield Lens Coating	Yes
FOV	40°
Range of Focus	0.25 m to infinity
Diopter Adjustment	-5 to +5
Controls	Digital
Automatic Brightness Control	Yes
Bright Light Cut-off	Yes
Automatic Shut-off System	Yes
Infrared Illuminator	Yes
IR Indicator	Yes (in FOV)
Low Battery Indicator	Yes (in FOV)
Power Supply	1 x 1.5 V AA type battery or 1 x 3 V CR123A type battery
Battery Life	50 hrs
Environmental Rating	Weather and fog resistant
Operating Temperature	-40 to +50 °C
Storage Temperature	-50 to +70 °C
Dimensions	172x62x102 mm / 6.7" x 2.5" x 4"
Weight	0.45 kg / 0.9 lbs

### TUBE SPECIFICATIONS

#### HIGH QUALITY 3 GEN IMAGE INTENSIFIER TUBE

DESCRIPTION	Standard
GENERATION	3
PHOTOCATHODE TYPE	GaAs
RESOLUTION, lp/mm*	64
SIGNAL TO NOISE RATIO*	22 Typical
FIGURE OF MERIT	1600 Typical
MTTF - MEAN TIME BEFORE FAILURE, hours	10,000
EXPORT	N/A for Export

\* Specifications are provided for informational purposes only. Actual values may vary



Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

1341 San Mateo Ave,  
South San Francisco, CA 94080.

[www.atncorp.com](http://www.atncorp.com)  
e-mail: [sales@atncorp.com](mailto:sales@atncorp.com), [info@atncorp.com](mailto:info@atncorp.com)

Tel: 800-910-2862, 650-989-5100,  
fax: 650-875-0129